



**Punjač i tester od 12 V pogodan za olovne i gel baterije.**



## PUNJAČ BATERIJA

- Automatsko punjenje bez nadzora.
- Održava punu napunjenost na 100% s plutajućim procesom.
- 2 razine struje punjenja (2 A / 5,5 A).
- Vidljiva razina napunjenosti (3 LED indikatora).
- Za startne akumulatore od 15 do 90 Ah.
- Zaštita ugrađene elektronike:
  - Zaštita od prenapona
  - Sigurno punjenje bez odspajanja baterije.



Integrirano skladište za kabele i stezaljke.



## ISPITIVAČ









- Stanje napunjenosti prikazano s 3 LED indikatora.

## SVEOBUHVAATNA ZAŠTITA



- Zaštita od promjene polariteta, kratkog spoja i preopterećenja.
- Zvučno upozorenje za sprječavanje promjene polariteta.
- Potpuno izolirane stezaljke.

CE - EN 60335-2-29

|  |  |  |  |  | Efficace/RMS | Moyen/Average (EN 60335) |  | IP |  |  |
|---|---|---|---|---|--------------|--------------------------|--|----|---|---|
| 50-60hz   |   | 12 V  | MIN. Ah<br>MAX.   | Reg   |              |                          | fuse   |    | cm  | kg  |
| 230 V   | 120 W   | 12 V  | 15-90 Ah  | 2 A   | 8 A          | 2-5.5 A                  | 15 A   | 20 | 12 x 17 x 29  | 3.4   |

Made in China

[www.gys.fr](http://www.gys.fr)